HM-RJ45-APT





Technical Parameters:

Insters:

- No. of contact: 8
- Rated current: 1A
- Rated voltage: 50V
- Rated impulse voltage: 0.8KV
- Pollution degree: 3
- Rated voltage acc.to UL/CSA: 30V
- Material: polycarbonate
- Temperature range: -40℃- +125℃
- Flammability acc.to UL 94: V0
- Mating cycles: ≥500
- Transmission features: category 6/Class E up to 500 MHz; acc. to ISO/IEC 24 702; ISO/IEC 11 801
- Transmissiong rate: 10/100/1000Mbit/10Gbit/s

技术参数:

插芯:

- 插针数: 8
- 额定电流: 1A
- 额定电压: 50V
- 额定脉冲电压: 0.8KV
- 污染等级: 3
- 依据UL/CSA的额定电压: ＜30V
- 材料: 聚碳酸酯
- 温度范围: -40℃- +125℃
- 依据UL 94的阻燃等级: V0
- 可拔插次数: ≥500
- 传输特性: 超6类可达500MHz 依据 ISO/IEC 24 702; ISO/IEC 11 801
- 传输速度: 10/100/1000Mbit/10Gbit/s
- 绝缘阻抗: ≥$10^{10}\Omega$



未注公差所依标准/Standard of tolerance					
公差等级 Tolerance lever	基本线性尺寸分段/Basic linear size segmentation				
	0.5~3	>3~6	>6~30	>30~120	>120~400
中等m	±0.1	±0.1	±0.2	±0.3	±0.5
公差等级 Tolerance lever	基本倒角尺寸分段/Basic chamfer size segmentation				
	0.5~3	>3~6	>6~30	>30	
中等m	±0.2	±0.5	±1	±2	
公差等级 Tolerance lever	基本角度尺寸分段/Basic angular dimension segmentation				
	~10	>10~50	>50~120	>120~400	
中等m	±1°	±30′	±20′	±10′	

				表面处理 Finish		—		图号 Drawing NO.	-
				材料 material		—		产品型号 Part Trpe	HM-RJ45-APT
标记 Mark	变更描述/Description	签名 Signature	日期 Date	比例 Scale	版本 REV	重量 Weight	数量 Qty.	产品料号 Part NO.	304507040002
	姓名/Name	日期/Data		1:1	B0			产品名称 Part Name	45芯壳体
绘图 Drawn	Yangzhen	25/11/01							
审核 Checked	Hongshuhao	25/11/01				All Dimensions in mm Original Size DIN A4		苏州威弗电气 SUZHOU WEVEL ELECTRICAL CO.,LTD	
批准 Approved									

档案员
日期